

# WKT SEALING COMPOUND

## CONSUMPTION CALCULATOR 310 ml cartridges

Number of cartridges (310 ml) required per qm Deck													
	Measures of the joint												
	Width ▶		4 mm			5 mm			6 mm			8 mm	
			0.012 ft			0.015 ft			0.018 ff			0.024 ft	
Depth ▶		6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	10 mm	12 mm	
		0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.030 ft	0.036 ft	
Width of the Planks ▶	30 mm	0,090 ft	2.3	3.0	3.8	2.8	3.7	4.6	3.2	4.3	5.4	-	-
	35 mm	0,105 ft	2.0	2.6	3.3	2.4	3.2	4.0	2.8	3.8	4.7	-	-
	40 mm	0,120 ft	1.8	2.3	2.9	2.2	2.9	3.6	2.5	3.4	4.2	-	-
	45 mm	0,135 ft	1.6	2.1	2.6	1.9	2.6	3.2	2.3	3.0	3.8	-	-
	50 mm	0,150 ft	-	-	-	1.8	2.3	2.9	2.1	2.8	3.5	4.5	5.3
	60 mm	0,180 ft	-	-	-	1.5	2.0	2.5	1.8	2.3	2.9	3.8	4.6
	70 mm	0,210 ft	-	-	-	1.3	1.7	2.2	1.5	2.0	2.5	3.3	4.0
	80 mm	0,240 ft	-	-	-	-	-	-	1.4	1.8	2.3	2.9	3.5
	90 mm	0,270 ft	-	-	-	-	-	-	1.2	1.6	2.0	2.6	3.2
	100 mm	0,300 ft	-	-	-	-	-	-	1.1	1.5	1.8	2.4	2.9
	110 mm	0,330 ft	-	-	-	-	-	-	1.0	1.3	1.7	2.2	2.6
120 mm	0,360 ft	-	-	-	-	-	-	0.9	1.2	1.5	2.0	2.4	

Consumption of WKT Sealing Compound per running meter joint													
	Measures of the joint												
	Width ▶		4 mm			5 mm			6 mm			8 mm	
			0.012 ft			0.015 ft			0.018 ff			0.024 ft	
Depth ▶		6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	10 mm	12 mm	
		0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.030 ft	0.036 ft	
WKT Sealing Compound per running meter joint ▶		24 ml	32 ml	40 ml	30 ml	40 ml	50 ml	36 ml	48 ml	60 ml	80 ml	96 ml	

Running meter joint per 310 ml cartridge													
	Measures of the joint												
	Width ▶		4 mm			5 mm			6 mm			8 mm	
			0.012 ft			0.015 ft			0.018 ff			0.024 ft	
Depth ▶		6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	10 mm	12 mm	
		0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.030 ft	0.036 ft	
Running meter joint per 310 ml Cartridge ▶		12.9 m	9.7 m	7.7 m	10.3 m	7.7 m	6.2 m	8.6 m	6.5 m	5.2 m	3.9 m	3.2 m	
		42.32 ft	31.82 ft	25.26 ft	33.79 ft	25.26 ft	20.34 ft	28.21 ft	21.32 ft	17.06 ft	12.79 ft	10.49 ft	

Consumption of WKT Primer depends strongly on several factors e.g. way of application, type of wood etc.. Therefore, it can only be roughly estimated with approx. 50 ml primer per 310 ml cartridge.

**Disclaimer:** This list is provided by PREMAPRO LLC to assist you. However, it is a rough calculation only. The exact product amount may differ due to surface and wood conditions and other circumstances that can not be take into account in this schedule. Deviations are possible and are not our responsibility. For more exact numbers, please perform a specific calculation based on your project. All Information listed is without guarantee. The manufacturer reserves the right to make technical and visual changes to this data.