

1. IDENTIFICATION OF THE PREPARATION AND COMPANY.

Product Name and Code : RETARDATION AGENT 0530-25004
Product use; Mix as appropriate (< 3%) with Coelan Boat Coating to slow curing process.
Name of the company:
COELAN[®]-FLÜSSIGKUNSTSTOFFE GmbH & Co. KG
Boschstraße 14-16
48653 COESFELD
Phone: (+49 2541) 920-0 Fax: (+492541) 920-400
Phone of the company: laboratory Phone:(+492541) 920-270
Emergency-Phone: (06132) 84463

2. COMPOSITION / INFORMATION ON INGREDIENTS.

Substances presenting a health hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Cas-No.	Names	Conc.	Symb.	R phrases
n.a.				

(See full text of R phrases under chapter 16)

3. HAZARDS IDENTIFICATION OF THE PREPARATION.

n.a.

n.a.

4. FIRST AID MEASURES.

General :

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation :

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

Eye contact :

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact :

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion :

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE-FIGHTING MEASURES.

Extinguishing media : recommended : alcohol resistant foam, CO₂, powders, water spray

Not to be used : water jet.

Recommendations : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water ways.

6. ACCIDENTAL RELEASE MEASURES.

Exclude sources of ignition and ventilate the area. Avoid breathing vapors. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

7. HANDLING AND STORAGE.

Handling.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits.

Additionally, the product should only be used in areas from which all bare electric lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Preparation may charge electro-statically: always use grounding leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the non-conducting type. Keep container tightly closed. Isolate from sources of heat, spark and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid inhalation of vapor and spray mist.

Smoking, eating and drinking should be prohibited in application area.

For personal protection see Section 8.

Never use pressure to empty the container as the container is not a pressure vessel. Always keep product material in original container. Comply with the health and safety at work laws.

Storage.

Although the storage and use of this product is not subject to specific statutory requirements, observation of the principles of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations as appropriate will be seen as good industrial practice in meeting the general duties of the Health and Safety at Work Act. Observe label precautions. Store between 5 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep away from sources of ignition. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION.

Engineering Measures.

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general air circulation. If these are not sufficient to maintain concentrations of particulate and solvent vapor below the OEL, suitable respiratory protection must be worn.

Exposure Limits.

Occupational exposure limit for :

CAS-No.	Names	STEL	LTEL
---------	-------	------	------

n.a.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Continued.

Personal Protection.

Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection:

For prolonged or repeated contact, use : Barrier creams may help to protect the exposed areas of the skin, they

should however not be applied once exposure has occurred.

Eye protection:

Use safety eyewear designed to protect against splash of liquids.

Skin protection:

Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

9. PHYSICAL AND CHEMICAL PROPERTIES.

Physical state : viscous.

Method:

Flash point : 65°C

DIN 53213

Viscosity : @ 23 °C

Specific gravity : 0.90

Vapor density : 1 heavier than air

Lower explosion limit: 0.8

Solubility in water : partial soluble

Volatile Organic Compounds: VOC = 897 g/l

10. STABILITY AND REACTIVITY.

Stable under recommended storage and handling conditions.(See section 7). When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. TOXICOLOGICAL INFORMATION.

There are no data available on the preparation itself. Exposure to component solvents vapors concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache; dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

12. ECOLOGICAL INFORMATION.

There are no data available on the preparation itself.
The product should not be allowed to enter drains or water ways.

13. DISPOSAL CONSIDERATIONS.

Do not allow into drains or watercourses.

EAK-Nr. Disposal name:
140603 Other solvents and solvent mixtures

Empty containers are to be given for disposal . Partially emptied containers are subject to special disposal regulations. In all cases and prior to disposal, check with your local waste regulatory agency.

14. TRANSPORT INFORMATION.

Transport only in accordance with ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

ADR/RID: Class: not a dangerous good item:
Transport document name: n.a.

IMDG: Class: n.a. UN Nr. : n.a.
EMS : n.a.
Proper shipping name :
Packaging group : n.a.
Marine pollutant : n.a. 0000000

ICAO/IATA: Class: n.a. UN Nr. : n.a.
Proper shipping name :
Packaging group : n.a.

15. REGULATORY INFORMATION.

The requirements of the Classification Packaging and Labeling of Dangerous Substances Regulations.
The product is labeled as follows :

Danger classification :
n.a.

Contains:
n.a.

R phrases:
n.a.

S phrases:
n.a.

other phrases:
n.a.

16. OTHER INFORMATION.

Full text of R phrases appearing in section 2 :
n.a.

The information contained in this Material Safety Data Sheet (MSDS) is based on the present state of knowledge and on current EEC and national law.

This MSDS is meant as a description of the safety requirements of the product and is not to be considered as a guarantee of the products' properties. The data in this MSDS does not establish a legally valid basis or foundation for any type of damage or liability claim.

As the users technical skill and project working conditions are beyond our knowledge and control, the product is not to be used for any other purposes than those specified under section 1, "Product Use", of this MSDS, without first obtaining written instructions and acknowledgment from the manufacturer.

The user is responsible for ensuring that the requirements and obligations of all relevant legislation and laws are complied with.

END